

**PT. PINDO DELI PAPER PRODUCTS
KARAWANG**



LABEL STOCK

ART PAPER HW PLUS/PWAT/WW01E

AR HP/PWAT/WW01E

Face Material (Art Paper)

Properties	Unit	Value	Test Method
Basis Weight	(g/m ²)	80 ± 4%	ISO 536
Thickness	(µm)	73 ± 5	ISO 534

Adhesive (PWAT)

Peel Adhesion (180°)	(N/25mm)	Min. 9	FINAT-FTM
Shear Force	(hours)	Min. 8	FINAT-FTM
Ball Tack	(Ball Number)	Min. 8	J. Dow Method

Backing Material (WW01E)

Basis Weight	(g/m ²)	82 - 89	ISO 536
Thickness	(µm)	96 ± 4	ISO 534

Service Temperature :

- 5 °C to 80 °C subject to facestock limitations

Shelf Life :

One year when stored at 23° C and 50 % RH

Application :

Multipurpose label with high quality paper, excellent printing and overprinting properties e.g thermal transfer. It also has good durability and weather-ability. works fine in Flexography, screen, letterpress, offset, electrophotography (cold fusion techniques), dot-matrix. No breakage or separation after stuck, Waterproof, no- tear features.

As wide range of applications, the customers should determine the suitability for specific purpose before using.

Revision :0
Issued Date: 12 September 2017

UNCONTROLLED COPY