

ROLL LABEL - POLYPROPYLENESIssue date : 05/01/2005
Date last modification : 27/09/2013**03022 RI-707/60 PP GLOSS WHITE TC AP901 WG62****Face Material**

Gloss white top coated polypropylene.

Type	Top coated polypropylene		
Colour and Finish	Gloss white		
Weight	54 g/m ² ±10%	ISO-536	
Thickness	60 µ ±10%	ISO 534-80	

Adhesive

Acrylic permanent adhesive featuring high clarity and cohesion with strong adhesion to apolar substrates (like PE and PP).

Reference	AP901		
Type	Acrylic permanent		
Min. Appl. Temp.	-5°C		
Service Temp.	-40°C/+120°C		
Shear	High		
Tack	8 N/25mm	FINAT FTM9	
Final Adhesion	7 N/25mm	FINAT FTM2	

This adhesive is approved by ISEGA (Direct contact dry & moist, non fatty foodstuffs) according to the German Recommendations XIV and complies with FDA 175.105.

Liner

Type	One side siliconised Glassine		
Colour and Finish	White		
Weight	62 g/m ² ±10%	ISO 536	
Thickness	55 µ ±10%	ISO 534	
Transparency	>45 %	DIN 53 147-64	

ApplicationsPrime labels for body care products, household chemicals, appliances and toys.
Not recommended for fan folder tags.**Printing Methods**Printable with letterpress UV, screenprinting UV and hot stamping.
Testing for suitability between media, printers and inks is always recommended prior to use.**Shelf life**36 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.



ROLL LABEL - POLYPROPYLENESIssue date : 13/01/2011
Date last modification : 27/09/2013**03147 RI-707/60 PP GLOSS CLEAR TC AP901 WG62****Face Material**

Gloss clear top coated polypropylene.

Type	Top coated polypropylene		
Colour and Finish	Gloss clear		
Weight	54 g/m ² ±10%	ISO-536	
Thickness	60 μ ±10%	ISO 534-80	

Adhesive

Acrylic permanent adhesive featuring high clarity and cohesion with strong adhesion to apolar substrates (like PE and PP).

Reference	AP901		
Type	Acrylic permanent		
Min. Appl. Temp.	-5°C		
Service Temp.	-40°C/+120°C		
Shear	High		
Tack	8 N/25mm	FINAT FTM9	
Final Adhesion	7 N/25mm	FINAT FTM2	

This adhesive is approved by ISEGA (Direct contact dry & moist, non fatty foodstuffs) according to the German Recommendations XIV and complies with FDA 175.105.

Liner

Type	One side siliconised Glassine		
Colour and Finish	White		
Weight	62 g/m ² ±10%	ISO 536	
Thickness	55 μ ±10%	ISO 534	
Transparency	>45 %	DIN 53 147-64	

ApplicationsPrime labels for body care products, household chemicals, appliances and toys.
Not recommended for fan folder tags.**Printing Methods**Printable with letterpress UV, screenprinting UV and gravure.
Testing for suitability between media, printers and inks is always recommended prior to use.**Shelf life**36 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

